

Normtoleranzen gemäss ISO / Tolérances normalisées selon ISO

h 6 / DIN 59361		
	≤	3 mm 0/-0.006 mm
>	3 ≤	6 mm 0/-0.008 mm
>	6 ≤	10 mm 0/-0.009 mm
>	10 ≤	18 mm 0/-0.011 mm
>	18 ≤	30 mm 0/-0.013 mm
>	30 ≤	50 mm 0/-0.016 mm

h7 / DIN 59360		
	≤	3 mm 0/-0.010 mm
>	3 ≤	6 mm 0/-0.012 mm
>	6 ≤	10 mm 0/-0.015 mm
>	10 ≤	18 mm 0/-0.018 mm
>	18 ≤	30 mm 0/-0.021 mm
>	30 ≤	50 mm 0/-0.025 mm

h8 / DIN 670		
	≤	3 mm 0/-0.014 mm
>	3 ≤	6 mm 0/-0.018 mm
>	6 ≤	10 mm 0/-0.022 mm
>	10 ≤	18 mm 0/-0.027 mm
>	18 ≤	30 mm 0/-0.033 mm
>	30 ≤	50 mm 0/-0.039 mm

h9 / DIN 671		
	≤	3 mm 0/-0.025 mm
>	3 ≤	6 mm 0/-0.030 mm
>	6 ≤	10 mm 0/-0.036 mm
>	10 ≤	18 mm 0/-0.043 mm
>	18 ≤	30 mm 0/-0.052 mm
>	30 ≤	50 mm 0/-0.062 mm

h10 / DIN 671		
	≤	3 mm 0/-0.040 mm
>	3 ≤	6 mm 0/-0.048 mm
>	6 ≤	10 mm 0/-0.058 mm
>	10 ≤	18 mm 0/-0.070 mm
>	18 ≤	30 mm 0/-0.084 mm
>	30 ≤	50 mm 0/-0.100 mm

h11 / DIN 668		
	≤	3 mm 0/-0.060 mm
>	3 ≤	6 mm 0/-0.075 mm
>	6 ≤	10 mm 0/-0.090 mm
>	10 ≤	18 mm 0/-0.110 mm
>	18 ≤	30 mm 0/-0.130 mm
>	30 ≤	50 mm 0/-0.160 mm

h12		
	≤	3 mm 0/-0.100 mm
>	3 ≤	6 mm 0/-0.120 mm
>	6 ≤	10 mm 0/-0.150 mm
>	10 ≤	18 mm 0/-0.180 mm
>	18 ≤	30 mm 0/-0.210 mm
>	30 ≤	50 mm 0/-0.250 mm

h13		
	≤	3 mm 0/-0.140 mm
>	3 ≤	6 mm 0/-0.180 mm
>	6 ≤	10 mm 0/-0.220 mm
>	10 ≤	18 mm 0/-0.270 mm
>	18 ≤	30 mm 0/-0.330 mm
>	30 ≤	50 mm 0/-0.390 mm

k11		
	≤	3 mm 0/+0.060 mm
>	3 ≤	6 mm 0/+0.075 mm
>	6 ≤	10 mm 0/+0.090 mm
>	10 ≤	18 mm 0/+0.110 mm
>	18 ≤	30 mm 0/+0.130 mm
>	30 ≤	50 mm 0/+0.160 mm
>	50 ≤	80 mm 0/+0.190 mm
>	80 ≤	120 mm 0/+0.220 mm
>	120 ≤	150 mm 0/+0.250 mm

k13		
	≤	3 mm 0/+0.140 mm
>	3 ≤	6 mm 0/+0.180 mm
>	6 ≤	10 mm 0/+0.220 mm
>	10 ≤	18 mm 0/+0.270 mm
>	18 ≤	30 mm 0/+0.330 mm
>	30 ≤	50 mm 0/+0.390 mm
>	50 ≤	80 mm 0/+0.460 mm
>	80 ≤	120 mm 0/+0.540 mm
>	120 ≤	150 mm 0/+0.630 mm